



Dimensions

| | |
|---|------------|
| A Length With Bucket | 3780 mm |
| B Width Over Tires | 1800 mm |
| E Ground Clearance | 250 mm |
| C Height To Top Of Cab | 2090 mm |
| D Wheelbase | 1250 mm |
| G Clearance At Max Lift And Dump | 2460 mm |
| H Reach At Max Lift And Dump | 900 mm |
| Turning Radius From Center - Inc Bucket | 2200 mm |
| Turning Radius From Center - Machine Rear | 1760 mm |
| Loadover Height | 2900 m |
| Dig Depth | 10000 mm |
| Dump Angle | 42 degrees |
| Dump Height | 2300 mm |
| Angle Of Departure | 29 degrees |
| Pin Height | 3200 m |
| Rollback - Ground Level | 30 degrees |

Specifications

| | |
|---|--------------------------------------|
| Tyres | |
| Standard | 12 x 16.5 - 10 PR Xtra Wall Off Road |
| Engine | |
| Emissions Certification | EPA-T4F (EU St3B) |
| Fuel | Diesel |
| Starter Motor | 4.2 KW |
| Battery | 12 V |
| Engine Oil Service Interval | 500 hours |
| Engine Make | 2257 |
| Engine Model | EcoMAX TCAE-55 |
| Gross Power | 55.2 kw |
| Cooling System | Liquid |
| Power Measured @ | 2400 rpm |
| Max Torque | 400 Nm |
| Torque Measured @ | 1200 rpm |
| Aspiration | Turbo |
| Displacement | 4.4 L |
| Operational | |
| Operational Weight | 4213 kg |
| Fuel Capacity | 103 L |
| Cooling System Fluid Capacity | 15.5 L |
| Engine Oil Fluid Capacity | 15 L |
| Hydraulic System Fluid Capacity | 55 L |
| Max Speed | 20 km/h |
| Chain Box Fluid Capacity - Each Side | 23 L |
| Operating Speed | 11 km/h |
| Tire Size | 12 x 16.5 |
| Operating Voltage | 12 V |
| Alternator Supplied Amperage | 95 amps |
| Transmission | |
| Model | Two Speed |
| Travel Speed | 20 km/h |

Loader

| | |
|---|--------------------|
| Loader Lift Capacity With Bucket | 2747 kg |
| Breakout Force | 2968 kg |
| Operating Load Rating | 1360.8 kg |
| Tipping Angle | 6369.1543 degrees |
| Bucket Capacity | 0.5 m ³ |
| Bucket Width | 1900 mm |

Hydraulic

| | |
|------------------------------|-----------|
| Pump Flow Capacity | 90 L/min |
| Relief Valve Pressure | 22994 kPa |

